

PC8900 Comparison Chart

Models	Application	Stages	Powering Method	Auto Changeover	Programming	Program Periods per Day	Indefinite Hold	Vacation Hold	Backlit Display	Programmable Fan	F/C Selectable	Filter Indication	Outdoor Sensor	Ventilation Control	Humidity Control	O & B Terminals	System "On" Indication	Auxiliary & Emergency Heat Indications	Honeywell Replacement
Honeywell																			
PC8900A1007/W8900A1004	SS/MS	Up to 2H/2C	HW	Y	7 Days	4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	LED	N/A	PC8900A1007/W8900A1004
PC8900A1007/W8900A1012	SS/MS	Up to 2H/1C	HW	Y	7 Days	4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	LED	N/A	PC8900A1007/W8900A1012
PC8900A1007/W8900B1002	HP	Up to 3H/2C	HW	Y	7 Days	4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	LED	Y	PC8900A1007/W8900B1002
PC8900A1007/W8900C1000	SS/MS	Up to 2H/2C	HW	Y	7 Days	4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	LED	N/A	PC8900A1007/W8900C1000
Carrier																			
Thermidistat	SS/HP/MS	Up to 3H/2C	HW	Y	7 Days	4	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	On the display	Y	PC8900/W8900

Legend: SS=single statge, HP=heat pump, MS=multistage, HW=hardwired, H=heat, C=cool, Y=yes, N=no, N/A=not applicable

